



REVISION RECORD			
REV	ECO	DESCRIPTION	DRFT DATE
Δ		Drawing amend	WF 01/06/06
Δ		增加VDE、CE认证标志	LJH 01/14/08

Notes:

1. Pitch: 7.50mm Poles: 2-12p
2. Rated voltage/current: UL 300V/15A VDE 400V/20A
3. Insulation resistance: 5000MΩ/DC1000V
4. Withstanding voltage: AC2000V/1min
5. Wire range: 28-12AWG 2.5mm²
6. Temp. Range: -40° C~+105° C
7. Torque: 4. 08kgf.cm (3. 61b. in)
8. Undimensioned Tolerances:

Pitch range in mm	Nominal dimension range in mm	
over 6	over 10	over 30
to 10	to 100	to 100
6	10	24
		30
		60
		100
		150
		±0.10
		±0.15
		±0.25
		±0.2±0.3
		±0.5±0.7
		±1.0±0.5/1.0

5	2EDG Contact	1005B00010(H)	XX	Phosphor bronze	Ni plated
4	DG128 Brass Cage	X000000020(H)	XX	Brass	Ni plated
3	2EDG " " Screws-M2.5	S000001370(H)	XX	Steel	Cr ³⁺ Zn
2	2EDGK-7.5-Cover	1017C0VXXA(H)	1	PA66	UL94V-0

DETACHED LISTS

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
1	2EDGK-7.5-Housing	1017A0VXXA(H)	1	PA66	UL94V-0

UNIT	MM	(INCH)
±0.1		
±0.05		
±0.02		
±0.01		

DATE	DRFT	DATE
10/07/05		

FINISH:	SCALE:	THIRD ANGLE PROJECTION
C: E	1: 1	