

# 8800 Thinline Rocker Switches

10A 250Vac



## Key Features

- ⬡ Ultra thin rocker switch
- ⬡ Ratings up to 15A, 250Vac
- ⬡ Single and twin gang
- ⬡ Panel cut out:  
Single 19.3 x 6.8  
Twin 19.3 x 13.4


## Approvals and specifications

- 10(6)A 250Vac T100 1E4 (10,000 Operations)  
6(2)A 250Vac T100 5E4 (50,000 Operations)  
Inrush rating 10/50A 1E4 (10,000 Operations)
  - UL CSA 15A 250Vac (Twin unit is 10A 250Vac)  
UL CSA 125Vac 1/2hp  
UL 100°C, file E45221, CSA file LR10990
- 3mm contact gap.


Terminal	Function	Rocker	Body	Body Colour	Rocker Colour
<p><b>H</b></p>	<p>Switches are ON when pressed over terminal 1</p> <p><b>8800</b></p> <p>ON - OFF Single pole</p>		<p>A. Single pole</p> <p>Panel Cut</p> <p>Bezel</p> <p>*Optional profile for orientation</p>	<p><b>B</b> Black</p>	<p><b>B</b> Black</p>
			<p><b>R</b> Red</p>	<p><b>R</b> Red</p>	
			<p><b>W</b> White</p>	<p><b>W</b> White</p>	
<p><b>T</b></p>	<p>Switches are ON when pressed over terminal 1 or 3</p>		<p>B. Single pole - Twin</p> <p>Panel Cut</p> <p>Bezel</p> <p>*Optional profile for orientation</p>	<p><b>B</b> Black</p>	<p><b>B</b> Black</p>
<p><b>X</b></p>	<p><b>8800</b></p> <p>ON - OFF Twin pole</p>		<p>Panel thickness</p> <p>0.75-1.2 1.25-1.99 2.00-3.00</p> <p>Dim X</p> <p>19.1/19.2 19.3/19.4 19.7/19.8</p> <p>Cut-outs must be punched in the direction of insertion</p>	<p><b>B</b> Black</p>	<p><b>B</b> Black</p>

## Dimensions

8800VA (H terminals shown)



8800V/8800VA (H terminals shown)



Legend	Legend Colour	Options
Blank	Blank	<p><b>Finish</b> Matt finish only.</p> <p><b>Colour</b> Call sales for custom colours. A full range is available for large orders.</p> <p><b>Legend printing</b> Select from the examples or call sales for custom legends.</p>
<b>132</b>	<b>B</b> Black	
	<b>W</b> White	

## Examples



☐ X8800VA



☐ X8800VA  
☐ T8800VA ---



☐ X8800VA  
☐ T8800VA ---



☐ H8800V/H8800VA  
☐ T8800V/T8800VA



☐ H8800V/H8800VA  
☐ T8800V/T8800VA