



- NOTES:
1. Pitch: 7.62mm
 2. Rated current: 15A
 3. Rated voltage: 300V
 4. Operation temperatures: -40° C ~ +105° C
 5. Insulation Withstand Voltage: AC2000V/1min
 6. Insulation Resistance: 500MΩ / DC500V
 7. Wire Range: 22~14AWG
 8. Max. Torque: 5.1kgf. cm
 9. Undimensioned Tolerances:

Pitch range in mm	Nominal dimension range in mm					
over 6	over 10	over 30	over 60	over 100	over 150	—
to 6	to 10	to 24	to 30	to 60	to 100	□
±0.10	±0.15	±0.25	±0.2±0.3	±0.5±0.7	±1.0	0.005/10



ITEM	NAME OF PART	QTY	MATERIAL	NOTES
1	DC25H-A Housing	1	PA66	UL94V-0
2	DC25H-Pin Header	XX	Brass	SnCe
3	3#6 bright-Screw	XX	Steel	Ni Plated

DEGSON	DEGSON ELECTRONICS CO., LTD.
NAME	DG25H-A-XXP-1Y-00A(H)
DRAWING NO.	DG25H-E03
REV	A3
DATE	12/06/07

DEGSON	22-14 AWG	2.5mm ²	ALUS
DEGSON	DG25	300V	15A