



Model: LP243454		Min. Capacity 最低容量(mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	320
Battery pack specification 电池组规格		Typical Capacity 典型容量(mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	350
		Nominal Voltage 标称电压(V)	3.7
		Internal Impedance 内阻(≦) (mΩ, AC 1KHZ)	250
Ambient Conditions 环境温度		Charge Temp. 充电温度(°C)	0~45
		Discharge Temp. 放电温度(°C)	-20~60
		Humidity(湿度)	65±20%

Overcharge Detection Voltage(V)		4.28±0.05
Overdischarge Detection Voltage(V)		2.3±0.1
Recommended Max loading /charging current		
建议最大负载/充电 peak value (loading)(A)	constant(loading) (A)	
持续(负载) 0.6 (A)	持续(负载) 0.3 (A)	
constant (charging) current(A)	持续(充电) 0.3 (A)	
Customer required Max loading /charging current		
客户要求最大的负载/充电电流		
peak value (loading)(A)	constant(loading) (A)	
峰值(负载) 0.6 (A)	持续(负载) 0.3 (A)	
constant (charging) current(A)	持续(充电) 0.3 (A)	

Remark(备注):
 1. No scratch, distortion, discoloration and leakage on the appearance of the cell (电池表面无划痕、变形、污点及漏液等现象).
 2. RoHS compliant(严格按照ROHS要求生产).

EEMB BATTERY		Drawn: ZS	Revise No.: E4-2009
Title	LP243454-PCM-LD	Group: Group46	Projection:
File NO.	A24309	Approved1:	Page: 1/1
		Approved2:	Scale: 1:2 : 1
		Draw Date: 2024/07/24	Unit: mm