



Model:	LP303248	
	Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	360
Battery pack specification 电池组规格	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	400
	Nominal Voltage 标称电压 (V)	3.7
	Internal Impedance 内阻 (≦) (mΩ, AC 1KHZ)	250
Ambient Conditions 环境温度	Charge Temp. 充电温度 (°C)	0~45
	Discharge Temp. 放电温度 (°C)	-20~60
	Humidity (湿度)	65±20%

Overcharge Detection Voltage (V)	4.28±0.05
	过充保护电压 (V)
Overdischarge Detection Voltage (V)	3.0±0.1
	过放保护电压 (V)
Recommended Max loading /charging current	
建议最大负载/充电峰值 (负载) (loading) (A)	constant (loading) (A)
持续 (负载) (A)	0.4 (A)
持续 (充电) (A)	0.4 (A)
Customer required Max loading /charging current	
客户要求最大的负载/充电电流峰值 (负载) (A)	constant (loading) (A)
持续 (负载) (A)	0.4 (A)
持续 (充电) (A)	0.4 (A)

**Battery protection Related Value:**  
(相关的电池保护值)

If actual application loading current is bigger than EEMB suggested please indicate. The application profile is important for an appropriate PCM design.  
(如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)

Remark (备注):  
1. No scratch, distortion, discoloration and leakage on the appearance of the cell (电池表面无划痕、变形、污点及漏液等现象).  
2. RoHS compliant (严格按照ROHS要求生产).

EEMB BATTERY		Drawn:	ZS	Revise No.:	E4-2009
Title	LP303248-PCM-LD	Group:	Group46	Projection:	
File NO.	A24310	Approved1:		Page:	1/1
		Approved2:		Scale:	1:2:1
		Draw Date:	2024/07/24	Unit:	mm