



| | | | | | |
|------------------------------------|--|---|--------|---|--------------------------|
| Model: LP382024 | | Min.Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量) | 140 | Overcharge Detection Voltage (V) | 4.28±0.05 |
| Battery pack specification (电池组规格) | | Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量) | 150 | Overdischarge Detection Voltage (V) | 3.0±0.1 |
| | | Nominal Voltage 标称电压 (V) | 3.7 | Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 (A) | constant (A) 持续 1 (A) |
| | | Internal impedance 内阻 (≅) (mΩ, AC 1KHz) | 400 | Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 (A) | constant (A) 持续 (A) |
| Ambient Conditions (环境温度) | | Charge Temp. 充电温度 (°C) | 0~45 | Battery protection (相关的电池保护值) If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要) | |
| | | Discharge Temp. 放电温度 (°C) | -20~60 | | |
| | | Humidity (湿度) | 65±20% | | |

Remark(备注):
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rohns compliant(严格按照ROHS要求生产).



| | | | | | |
|----------|-----------------|------------|------------|-------------|---------|
| Title | LP382024-PCM-LD | Drawn: | Helingling | Revise No.: | E4-2009 |
| File NO. | A04681 | Checked 1: | Helen | Projection: | |
| | | Checked 2: | Keyan | Page: | 1/1 |
| | | Approved: | | Scale: | 2 : 1 |
| | | Draw Date: | 2011/05/20 | Unit: | mm |