



Model: LP384765		Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	1050
Battery pack specification (电池组规格)		Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	1150
		Nominal Voltage 标称电压 (V)	3.7
		Internal impedance 内阻 (≦) (m <sup>2</sup> , AC 1KHz)	200
Ambient Conditions (环境温度)		Charge Temp. 充电温度 (°C)	0~45
		Discharge Temp. 放电温度 (°C)	-20~60
		Humidity (湿度)	65±20%
		<b>Battery protection</b> <b>Related Value:</b> <b>(相关的电池保护值)</b>	
		Overcharge Detection Voltage (V) 过充保护电压 (V)	4.28±0.05
		Overdischarge Detection Voltage (V) 过放电保护电压 (V)	2.3±0.1
		Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 2.0 (A)	constant (A) 持续 1.0 (A)
		Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 _____ (A)	constant (A) 持续 _____ (A)
<small>If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于 EEMB 提供值, 请提出来, 实际的应用情况对 PCM 的设计至关重要)</small>			

Remark(备注):  
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell/电池表面无划痕、变形、污点及漏液等现象).  
 2. Rohs compliant(严格按照ROHS要求生产).

Title		LP384765-PCM-LD	
File NO.		A13233	
<b>EEMB BATTERY</b>			
Drawn:	Leiyuanchao	Revise No.:	E4-2009
Checked 1:	Catherine	Projection:	
Checked 2:		Page:	1/1
Approved:		Scale:	1 : 1.8
Draw Date:	2016/09/21	Unit:	mm