



Model: LP603026		Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	400	Overcharge Detection Voltage(V)	4.28±0.05
Battery pack specification 电池组规格		Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	420	Overdischarge Detection Voltage(V)	3.0±0.1
		Nominal Voltage 标称电压 (V)	3.7	过放保护电压 (V)	Limited to Max loading current
		Internal impedance 内阻 (≦) (m ,AC 1KHz)	250	Customer required Max loading current 客户要求最大的负载电流	constant (A) 持续 0.42 (A)
Ambient Conditions (环境温度)		Charge Temp. 充电温度(°C)	0~45	峰值 0.82 (A)	持续 0.42 (A)
		Discharge Temp. 放电温度(°C)	-20~60	If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于 EEMB 提供值, 请提出来, 实际的应用情况对 PCM 的设计至关重要)	
		Humidity(湿度)	65±20%	Battery protection (相关的电池保护值)	

Remark(备注):
 1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rols compliant(严格按照ROHS要求生产).

1 2 3 4 5 6

Title		EEMB BATTERY		Drawn:	Yanf	Revise No.:	E4-2009
File NO.		LP603026-PCM-LD		Group:	Group1	Projection:	
		A17126		Approved1:		Page:	1/1
				Approved2:		Scale:	1.5 : 1
				Draw Date:	2019/05/13	Unit:	mm

