



(Scale: 1:2:1)

Model: LP603449		Overcharge Detection Voltage(V) 过充保护电压(V)	4.28±0.05
Min.Capacity 最低容量 (mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)		Overdischarge Detection Voltage(V) 过放保护电压(V)	3.0±0.1
Typical Capacity 典型容量 (mAh) (0.2C,25±3°C) ※Single cell capacity (单体电芯容量)		Limited to Max loading current 仅用于最大的负载电流 peak value (A) 峰值 2 (A)	constant (A) 持续 1 (A)
Nominal Voltage 标称电压 (V)		Customer required Max loading current 客户要求最大的负载电流 peak value (A) 峰值 2 (A)	constant (A) 持续 1 (A)
Internal impedance 内阻(≤) (mΩ,AC 1KHz)		Battery protection 相关的电池保护(值)	
Charge Temp. 充电温度(°C)		Ambient Conditions (环境温度)	
Discharge Temp. 放电温度(°C)		Humidity(湿度)	
0~45		65±20%	

Title File NO.		LP603449-PCM-LD A05313	
Drawn:		Yinjie	
Checked 1:		Jessie	
Checked 2:			
Approved:			
Draw Date:		2011/10/20	
Revision No.:		E4-2009	
Projection:		1/1	
Page:		1/1	
Scale:		1:1	
Unit:		mm	

Remark(备注):
1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
2. RoHS compliant(严格按照ROHS要求生产)

1 2 3 4 5 6