



Model: LP603450HA		Overcharge Detection Voltage(V)	4.28±0.05
Battery pack specification (电池组规格)	Min. Capacity 最低容量 (mAh) (0.2C, 25±3°C)	过充保护电压 (V)	3.0±0.1
	Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C)	过放电保护电压 (V)	
	850	过放电保护电压 (V)	
	900	Limited to Max loading current 仅用于最大的负载电流	
	3.7	峰值 9.0 (A)	constant (A) 持续 4.5 (A)
	250	客户要求的最大负载电流	constant (A) 持续 (A)
		Battery protection (相关的电池保护值)	
		If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design. (如果实际应用的负载电流大于 EEMB 提供值, 请提出来, 实际的应用情况对 PCM 的设计至关重要)	
Ambient Conditions (环境温度)	Charge Temp. 充电温度 (°C)	0~45	
	Discharge Temp. 放电温度 (°C)	-20~60	
	Humidity (湿度)	65±20%	

EEMB BATTERY		Drawn:	Leiyuanhao	Revise No.:	E4-2009
Title	LP603450HA-PCM-LD	Checked 1:	Catherine	Projection:	
File NO.	A13209	Checked 2:		Page:	1/1
		Approved:		Scale:	1 : 1
		Draw Date:	2016/09/14	Unit:	mm

Remark(备注):
 1. No scratch/distortion/dicoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
 2. Rohs compliant(严格按照ROHS要求生产).

1
2
3
4
5
6