

TSM7P06CP

60V P-Channel Power MOSFET

TO-252



Pin Definition:

1. Gate
2. Drain
3. Source

Key Parameter Performance


Parameter	Value	Unit
V_{DS}	-60	V
$R_{DS(on)}$ (max)	$V_{GS} = -10V$	180
	$V_{GS} = -4.5V$	220
Q_g	8.2	nC

Ordering Information

Part No.	Package	Packing
TSM7P06CP ROG	TO-252	2.5kpcs / 13" Reel

Note: "G" denotes for Halogen- and Antimony-free as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds

Block Diagram



P-Channel MOSFET

Absolute Maximum Ratings ($T_C=25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-60	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current	I_D	$T_C = 25^\circ C$	-7
		$T_C = 100^\circ C$	-4.4
Pulsed Drain Current ^(Note 1)	I_{DM}	-28	A
Single Pulse Avalanche Energy ^(Note 2)	E_{AS}	32	mJ
Single Pulse Avalanche Current ^(Note 1)	I_{AS}	-8	A
Power Dissipation @ $T_C = 25^\circ C$	P_D	15.6	W
Operating Junction Temperature	T_J	150	$^\circ C$
Storage Temperature Range	T_{STG}	-50 to +150	$^\circ C$

Thermal Performance

Parameter	Symbol	Limit	Unit
Thermal Resistance - Junction to Case	$R_{\theta JC}$	8	$^\circ C/W$
Thermal Resistance - Junction to Ambient	$R_{\theta JA}$	62	









Electrical Specifications (T_C=25°C unless otherwise noted)

Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = -250μA	BV _{DSS}	-60	--	--	V
Drain-Source On-State Resistance	V _{GS} = -10V, I _D = -3A	R _{DS(ON)}	--	153	180	mΩ
	V _{GS} = -4.5V, I _D = -1.5A		--	198	220	
Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = -250μA	V _{GS(TH)}	-1.2	-1.6	-2.5	V
Zero Gate Voltage Drain Current	V _{DS} = -60V, V _{GS} = 0V	I _{DSS}	--	--	-1	μA
	V _{DS} = -48V, V _{GS} = 0V, T _C = 125°C		--	--	-10	
Gate Body Leakage	V _{GS} = ±20V, V _{DS} = 0V	I _{GSS}	--	--	±100	nA
Forward Transconductance ^(Note 3)	V _{DS} = -10V, I _D = -2A	g _{fs}	--	3	--	S
Dynamic						
Total Gate Charge ^(Note 3,4)	V _{DS} = -30V, I _D = -3A, V _{GS} = -10V	Q _g	--	8.2	--	nC
Gate-Source Charge ^(Note 3,4)		Q _{gs}	--	1.8	--	
Gate-Drain Charge ^(Note 3,4)		Q _{gd}	--	1.5	--	
Input Capacitance	V _{DS} = -30V, V _{GS} = 0V, f = 1.0MHz	C _{iss}	--	425	--	pF
Output Capacitance		C _{oss}	--	35	--	
Reverse Transfer Capacitance		C _{rss}	--	20	--	
Switching						
Turn-On Delay Time ^(Note 3,4)	V _{DD} = -30V, I _D = -1A, R _{GEN} = 6Ω	t _{d(on)}	--	5.2	--	ns
Turn-On Rise Time ^(Note 3,4)		t _r	--	19	--	
Turn-Off Delay Time ^(Note 3,4)		t _{d(off)}	--	35	--	
Turn-Off Fall Time ^(Note 3,4)		t _f	--	10.6	--	
Source-Drain Diode Ratings and Characteristic						
Maximum Continuous Drain-Source Diode Forward Current	Integral reverse diode in the MOSFET	I _S	--	--	-7	A
Maximum Pulse Drain-Source Diode Forward Current		I _{SM}	--	--	-28	A
Diode-Source Forward Voltage	V _{GS} = 0V, I _S = -1A	V _{SD}	--	--	-1	V

Note:


1. Pulse width limited by safe operating area
2. L=1mH, I_{AS} = -8A, V_{DD} = -25V, R_G = 25Ω, Starting T_J = 25°C
3. Pulse test: pulse width ≤300μs, duty cycle ≤2%
4. Switching time is essentially independent of operating temperature.

Electrical Characteristics Curve






TO-252 Mechanical Drawing



Unit: Millimeters

Marking Diagram



- Y** = Year Code
- M** = Month Code for Halogen Free Product
(**O**=Jan, **P**=Feb, **Q**=Mar, **R**=Apr, **S**=May, **T**=Jun, **U**=Jul, **V**=Aug, **W**=Sep, **X**=Oct, **Y**=Nov, **Z**=Dec)
- L** = Lot Code

TSM7P06CP

60V P-Channel Power MOSFET

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Taiwan Semiconductor:](#)

[TSM7P06CP ROG](#)